

SATAKE

DRUM DETACHER SDD





The Satake Drum Detacher SDD is used for the gentle disruption of endosperm flakes without disintegrating any bran and germ particles present. It is particularly useful on tail end reduction passages for increasing flour releases without causing any significant increase in ash or colour.


Installation

The Satake Drum Detacher may be floor mounted, suspended from a ceiling or mounted on a frame as an in-line assembly.

Type	Capacity (kg/h)	Motor (kW)	Weight (kg)	Dimensions (mm)				
				A	B	C	Inlet (O/D)	Outlet (O/D)
SDD30A	1,000	2.2	80	633	636	477	127	127



All Satake products are the subject of continuous development and, as a result, their specification may change and differ in detail from that outlined in this leaflet.



Hiroshima, Japan
Houston, U.S.A.
Stockport, England

Tel: +81 824 20 8560
Tel: +1 713 772 8400
Tel: +44 161 406 3800

Fax: +81 824 20 0865
Fax: +1 713 772 8484
Fax: +44 161 406 3801

www.satake-japan.co.jp
www.satake-usa.com
www.satake.co.uk

JDG02056@nifty.ne.jp
cereal@satake-usa.com
sales@satake.co.uk

SATAKE

Building on a Tradition of Excellence